

1/2" One Way Shut-Off - 5 Series



INDUSTRIAL INTER-CHANGE

- Meets ISO 6150-B
- ANSI(NFPA) T3.20.14-1990
- The SV Series Meets ISO 4414

| | Plugs | | | Manual | Automatic complies with A-A-59439 | Safety | Coaxial Plug | Coaxial Coupler |
|------------------------------------|----------|-----------------------------------|--------------------|----------|--------------------------------------|----------|---|-----------------|
| | | | | | | | | |
| Size | Cat. No. | Cat. No. | Cat. No. | Cat. No. | Cat. No. | Cat. No. | Cat. No. | Cat. No. |
| Female Thread | | | | | | | The Coaxial safety sockets and plugs are for use on single point injection lubrication systems. | |
| 1/4 FPT | - | | | 4015 | FM4015 | - | | - |
| 3/8 FPT | 53-5 | | | 5005 | FM5005 | SV5005 | | SV5205CA |
| 1/2 FPT | 55-5 | | | 5205 | FM5205 | SV5205 | | - |
| 3/4 FPT | 57-5 | | | 5405 | FM5405 | SV5405 | | - |
| Male Thread | | Free Swivel [1] Under Pressure | Ball Check Plug[2] | | | | | |
| 1/4 MPT | 50-5 | | | 4905 | FM4905 | - | | |
| 3/8 MPT | 52-5 | | | 5105 | FM5105 | SV5105 | | |
| 1/2 MPT | 54-5 | 54S-5 | 54-5G | 5305 | FM5305 | SV5305 | 54-5CA | SV5305CA |
| 1/2 MPT [Brass] | 54-5B | | 54-5GB | - | - | - | | - |
| 3/4 MPT | 56-5 | | | 5505 | FM5505 | SV5505 | | SV5505CA |
| Hose Stem (Require Hose Clamps) | | | | | | | [1] Swivel Plugs – Eliminates hose twist for applications such as blow guns, air tools, etc. | |
| 1/4 I.D. | - | | | 5605 | FM5605 | - | [2] Ball check plugs eliminate hose whip at disconnect by checking the rapid flow of downstream exhaust air | |
| 3/8 I.D. | 59-5 | | | 5705 | FM5705 | SV5705 | [3] BL – Locks manual socket against accidental disconnect. | |
| 1/2 I.D. | 60-5 | | 60-5G | 5805 | FM5805 | SV5805 | [4] SL – Locks automatic socket against accidental disconnect. | |
| 1/2 I.D. [Brass] | 60-5B | | | - | - | - | To order, prefix BL to socket number. | |
| 3/4 I.D. | 61-5 | | | 5905 | FM5905 | SV5905 | To order, change FM prefix to SL. | |
| Push-On Hose Stem | | | | | | | [5] Protective Cover for Safety Series Coupler – Yellow Cat. No. SV5-PC – For use with "SV5" Sockets | |
| 3/8 I.D. | 71-5 | | | - | - | - | | |
| 1/2 I.D. | 81-5 | | | 1815 | FM1815 | - | | |
| 1/2 I.D. [Brass] | 81-5B | | | - | - | - | | |
| Reusable Hose Clamp ID x OD | | | | | | | <ul style="list-style-type: none"> • Superior cushioning effect of Plastisol cover provides better protection for auto, motorcycle, marine, & appliance finishes. • Flexible protective cover allows normal coupling operation while reducing the entry of contaminants in dirty environments. • Standard SV couplers with protective covers are less expensive than competitive hard plastic models, plus they eliminate the need to stock both standard and plastic bodied couplers. | |
| 1/4 x 1/2 | PB3-5 | | | | | | | |
| 1/4 x 9/16 | PB5-5 | | | | | | | |
| 1/4 x 5/8 | PB7-5 | | | | | | | |
| 1/4 x 11/16 | PB9-5 | | | | | | | |
| 3/8 x 5/8 | PD7-5 | | | SD7-5 | FM5SD7-5 | | | |
| 3/8 x 11/16 | PD9-5 | | | SD9-5 | FM5SD9-5 | | | |
| 3/8 x 3/4 | PD11-5 | | | SD11-5 | FM5SD11-5 | | | |
| 3/8 x 13/16 | PD13-5 | | | SD13-5 | FM5SD13-5 | | | |
| 1/2 x 13/16 | PP13-5 | | | SP13-5 | FM5SP13-5 | | | |
| 1/2 x 7/8 | PP15-5 | | | SP15-5 | FM5SP15-5 | | | |
| 1/2 x 15/16 | PP17-5 | | | SP17-5 | FM5SP17-5 | | | |
| 1/2 x 1 | PP19-5 | | | SP19-5 | FM5SP19-5 | | | |

- Profile drawings available at www.couplers.com
- See Page 68 for Specifications, Performance Data, Full Size Templates, and Optional Seal Compounds

COUPLERS & ACCESSORIES

CLAMPING PRODUCTS

COUPLER SPEC'S & LAYOUTS

TECHNICAL DATA

INDEX