

# 1/4" One Way Shut-Off - 3 Series



## INDUSTRIAL INTERCHANGE

- Meets ISO 6150-B
- ANSI (NFPA) T3.20.14-1990
- The SV Series Meets ISO 4414

Standard Plugs	Ball Check Plugs	Valve Core Plugs	Manual Industrial	Automatic Complies with A-A-59439	Manual Sleeve Guard	Safety

Size	Cat. No.	Cat. No.	Cat. No.	Cat. No.	Cat. No.	Cat. No.	Cat. No.	Cat. No.
<b>Female Thread</b>								
1/8 FPT	13-3				2803	FM2803	SG2803	-
1/8 FPT [Brass]	13-3B				-	-	-	-
1/8 FPT [303 Stainless]	13-3S/S				2803S/S	-	-	-
1/4 FPT	11-3	-	-	-	3003	FM3003	SG3003	SV3003
1/4 FPT [Brass]	11-3B				-	-	-	-
1/4 FPT [303 Stainless]	11-3S/S				3003S/S	-	-	-
3/8 FPT	15-3				3203	FM3203	SG3203	SV3203
3/8 FPT [303 Stainless]	-				3203S/S	-	-	-
<b>Male Thread</b>		<b>Free Swivel Under Pressure [3]</b>	<b>Ball Check Plug [1]</b>	<b>Valve Core Plug [2]</b>				
1/8 MPT	12-3	12S-3	-	-	2903	FM2903	SG2903	-
1/8 MPT [Brass]	12-3B	-	-	-	-	-	-	-
1/8 MPT [303 Stainless]	12-3S/S	-	-	-	2903S/S	-	-	-
1/4 MPT	10-3	10S-3	10-3G	10-3D	3103	FM3103	SG3103	SV3103
1/4 MPT [Spring Loaded]	-	-	10-3GS	-	-	-	-	-
1/4 MPT [Brass]	10-3B	-	10-3GB	10-3DB	-	-	-	-
1/4 MPT [303 Stainless]	10-3S/S	-	10-3GS/S	-	3103S/S	-	-	-
3/8 MPT	14-3	14S-3	14-3GB	-	3303	FM3303	SG3303	SV3303
3/8 MPT [Brass]	14-3B	-	-	-	-	-	-	-
3/8 MPT [303 Stainless]	-	-	-	-	3303S/S	-	-	-
<b>Hose Stem (Requires Hose Clamps)</b>								
1/4 I.D.	16-3				3603	FM3603	SG3603	SV3603
1/4 I.D. [Brass]	16-3B				-	-	-	-
1/4 I.D. [303 Stainless]	-				3603S/S	-	-	-
5/16 I.D.	165-3				3653	FM3653	-	-
3/8 I.D.	17-3				3703	FM3703	SG3703	SV3703
3/8 I.D. [Brass]	17-3B				-	-	-	-
3/8 I.D. [303 Stainless]	-				3703S/S	-	-	-
<b>Push-On Hose Stem</b>								
1/4 I.D.	51-3				1513	FM1513	SG1513	-
3/8 I.D.	71-3				1713	FM1713	SG1713	-
<b>Reusable Hose Clamp ID x OD</b>								
1/4 x 1/2	PB3-3				SB3-3	FMSB3-3		
1/4 x 1/2 [Brass]	PB3-3B				-	-		
1/4 x 1/2 [303 Stainless]	PB3-3S/S				SB3-3S/S	-		
1/4 x 9/16	PB5-3				SB5-3	FMSB5-3		
1/4 x 9/16 [Brass]	PB5-3B				-	-		
1/4 x 5/8	PB7-3				SB7-3	FMSB7-3		
1/4 x 5/8 [Brass]	PB7-3B				-	-		
1/4 x 5/8 [303 Stainless]	PB7-3S/S				SB7-3S/S	-		
1/4 x 11/16	PB9-3				SB9-3	FMSB9-3		
1/4 x 11/16 [Brass]	PB9-3B				-	-		
5/16 x 9/16	PC5-3				SC5-3	FMSC5-3		
5/16 x 5/8	PC7-3				SC7-3	FMSC7-3		
3/8 x 5/8	PD7-3				SD7-3	FMSD7-3		
3/8 x 11/16	PD9-3				SD9-3	FMSD9-3		
3/8 x 3/4	PD11-3				SD11-3	FMSD11-3		
3/8 x 13/16	PD13-3				SD13-3	FMSD13-3		

- [1] Ball check plugs eliminate hose whip at disconnect by checking the rapid flow of downstream exhaust air
- [2] Sockets with modified valves are recommended for use with valve core plugs. Suffix-D to socket Cat. No.
- [3] Swivel Plugs - Eliminates hose twist on end drop applications such as blow guns, air tools, etc.
- [4] BL - Locks manual socket against accidental disconnect. To order, prefix BL to socket number.
- [5] SL - Locks automatic socket against accidental disconnect. To order, change FM prefix to SL.



Dust Caps, Plugs  
3PDC



Dust Caps, Sockets  
3SDC

- Profile drawings available at [www.couplers.com](http://www.couplers.com)
- See Page 68 for Specifications, Performance Data, Full Size Templates, and Optional Seal Compounds