



3/4" One Way Shut-Off – 6 Series

INDUSTRIAL INTERCHANGE

- Meets ISO 6150-B
- ANSI(NFPA)
T3.20.14-1990
- The SV Series Meets ISO 4414

Plugs	Automatic	Safety	Coaxial Plug	Coaxial Coupler

Size	Cat. No.	Cat. No.	Cat. No.	Cat. No.	Cat. No.
Female Thread		 SL optional [1]		The Coaxial safety sockets and plugs are for use on single point injection lubrication systems.	
1/2" FPT	65-6	FM6206	–	–	–
3/4" FPT	67-6	FM6406	SV6406		SV6406CA
1" FPT	69-6	FM6606	SV6606		–
Male Thread					
1/2" MPT	64-6	FM6306	–	64-6CA	–
3/4" MPT	66-6	FM6506	SV6506	66-6CA	SV6506CA
1" MPT	68-6	FM6706	SV6706	–	–
Hose Stem (Require Hose Clamps)				[1] SL – Locks automatic socket against accidental disconnect. To order, change FM prefix to SL.	
1/2" I.D.	70-6	FM6806	–		
3/4" I.D.	71-6	FM6906	SV6906		
1" I.D.	72-6	FM7006	–		

- Profile drawings available at www.couplers.com
- See Page 68 for Specifications, Performance Data, Full Size Templates