





Swivel [Free Swivel Under Pressure]

90° Swivel	
	
Size	Cat. No.
1/4 MPT x 1/4 FPT	25US90

Male Barbed Insert	
	
Size	Cat. No.
1/4 MPT x 1/4 ID	M7S
3/8 MPT x 3/8 ID	M13S
1/2 MPT x 1/2 ID	M17S

Push-On Swivel	
	
Size	Cat. No.
1/4 MPT x 1/4 ID	PM7S
3/8 MPT x 3/8 ID	PM13S
1/2 MPT x 1/2 ID	PM17S

Male to Female Pipe	
	
Size	Cat. No.
1/4 MPT x 1/4 FPT	25US
3/8 MPT x 3/8 FPT	38US
1/2 MPT x 1/2 FPT	50US

360 Degree Universal Swivel [1/4", 3/8" and 1/2" Body]

Benefits

- Dual Series swivel 360° in two independent planes
- Allows air hose to hang straight down when used with air tools
- Reduces operator fatigue
- Reduces the possibility of carpal tunnel syndrome
- Increases air hose life
- Patented non-marring series (plastic encapsulated) is ideal when non-marring and scratch reduction is needed

Pipe size: 1/4" NPT male x 1/4" NPT female

Maximum Working Pressure: 300 PSIG





Materials of Construction:

- Body: Brass and plated steel
- Seals: Buna-N

NOTE: When used with percussion tools, a minimum of 18" of hose between tool and swivel is required.

Universal Swivels:

- reduces operator fatigue
- increases air hose life

	Brass/Steel Dual Swivel	Non-Marring Dual Swivel	Non-Marring Single Swivel	Standard Swivel (Without Plastic Covering)
				
Size	Cat. No.	Cat. No.	Cat. No.	Cat. No.
1/4" FPT x 1/4" MPT	25US36	—	—	190026A
3/8" FPT x 1/4" MPT	—	190010A	190040	190029A
3/8" FPT x 3/8" MPT		190011A	190041	190027A
1/2" FPT x 1/2" MPT		190012	190042	190028