


# Clearflo®

Clear PVC Tubing  
Fuel & Oil Grade PVC Tubing




**ESOP** Employee Owned  
for Your Benefit

**NEWAGE  
INDUSTRIES**

Fluid Transfer Specialists®

## Clear PVC Tubing



- Made from non-toxic ingredients conforming to FDA and 3A standards\*
- PVC compound meets USP Class VI requirements\*
- Listed by the National Sanitation Foundation (NSF 51) for food equipment materials\*
- Glass-like clarity\* with mirror-smooth surface provides outstanding flow characteristics
- Does not impart a taste or odor\*
- Lightweight yet tough and abrasion resistant
- As flexible as rubber
- Handles a wide variety of chemicals, gases, and liquids
- Material meets UL94 HB burn rating
- Special Fuel & Oil grade available



\*Clear only

### Notes

CLEARFLO is generally unaffected by most oxidizing and reducing agents. Diluted acids and alkalies have little effect, though if highly concentrated they tend to make the tubing less pliable. If chemical resistance is of major concern, in-plant tests are suggested.

In clean applications, CLEARFLO's smooth surface prevents lodging of bacteria and sediment buildup. It is easily drained and flushed clean with most available cleaning and sanitizing agents.

Transparent yellow CLEARFLO FUEL & OIL was created to extend the working life of PVC tubing in fuel and oil applications. Gasoline and oils harden standard PVC over periods of intermittent use, but CLEARFLO FUEL & OIL is specially formulated to prevent hardening.

### Physical Properties\*\*

	Fuel & Oil	Clear
Hardness, Shore A $\pm 5$	62	68
Tensile Strength, psi	1980	1900
Elongation at Break, %	730	400
Brittle Temperature, °F	-20	-41
Maximum Operating Temp., °F	175	175

\*\*Values listed are typical for the material used in manufacture, except where noted, and are meant only as a guide to aid in design. Field testing should be performed to find the actual values for your application.



### CLEARFLO FUEL & OIL – Transparent Yellow†

PART NO.	ID (IN.)	OD (IN.)	WALL (IN.)	STANDARD LENGTH (FT.)	WORKING PSI AT 70°F	BURST PSI AT 70°F	LBS. PER 100 FT.
111 0032	1/8	1/4	1/16	50	68	204	2.1
111 0067	3/16	5/16	1/16	50, 100	55	165	2.8
111 0102	1/4	3/8	1/16	50, 100	55	165	3.5
111 0137	3/8	1/2	1/16	50	40	120	4.9
111 0172	1/2	3/4	1/8	50	45	135	12.8

†Specially formulated to remain flexible when used with fuels and oils. NOT NSF LISTED. For industrial applications only.

Add length suffix to part number when ordering. Example: 50 ft. of 1/8" I.D. x 1/4" O.D. tubing is part number 111 0032-50. Sold by standard coil length only.

**BOLD** indicates the critical dimension for fittings application.

### Custom Services

- **Cut**
- **Color**
- **Hot Bond**
- **Hardness**
- **Size**
- **Overbraid**
- **Heat-Form**
- **And More**

Call for more information: **800-506-3924** or **215-526-2300**

## Clear PVC Tubing

## CLEARFLO – Clear

PART NO.	ID (IN.)	OD (IN.)	WALL (IN.)	STANDARD LENGTH (FT.)	WORKING PSI AT 70°F	BURST PSI AT 70°F	LBS. PER 100 FT.
110 0071	1/16	1/8	1/32	500	33	132	.51
110 0225	3/32	5/32	1/32	500	42	168	.68
110 0379	1/8	3/16	1/32	500	44	176	.85
110 0456	1/8	1/4	1/16	100, 500	68	272	2.10
110 0841	3/16	1/4	1/32	100	33	132	1.2
110 0918	3/16	5/16	1/16	100, 500	55	220	2.7
110 0995	3/16	3/8	3/32	100	70	280	4.6
110 1149	1/4	3/8	1/16	50, 100, 500	55	220	3.4
110 1226	1/4	7/16	3/32	100	60	240	5.7
110 1303	1/4	1/2	1/8	100	70	280	8.3
110 1380	5/16	7/16	1/16	100, 500	50	200	4.2
110 1457	5/16	1/2	3/32	100	60	240	6.8
110 1534	5/16	9/16	1/8	100	70	280	9.7
110 1611	3/8	1/2	1/16	100, 500	40	160	4.8
110 1688	3/8	9/16	3/32	100	50	200	7.8
110 1765	3/8	5/8	1/8	100	65	260	11.1
110 1842	3/8	3/4	3/16	100	66	264	18.7
110 2150	7/16	11/16	1/8	100	50	200	12.5
110 2227	1/2	5/8	1/16	100, 500	30	120	6.2
110 2304	1/2	11/16	3/32	100	40	160	9.9
110 2381	1/2	3/4	1/8	100	45	180	13.9
110 2689	9/16	3/4	3/32	100	40	160	11.0
110 2920	5/8	3/4	1/16	100	20	80	7.6
110 2997	5/8	13/16	3/32	100	35	140	12.0
110 3074	5/8	7/8	1/8	50, 100	40	160	16.6
110 3151	5/8	15/16	5/32	100	50	200	21.7
110 3536	3/4	7/8	1/16	100	19	76	9.0
110 3613	3/4	1	1/8	50, 100	35	140	19.4
110 3690	3/4	1-1/16	5/32	100	40	160	25.1
110 3767	3/4	1-1/8	3/16	100	44	176	31.2
110 3844	3/4	1-1/4	1/4	100	44	176	44.3
110 3921	7/8	1-1/8	1/8	100	30	120	22.1
110 4152	1	1-1/4	1/8	50, 100	28	112	25.0
110 4306	1	1-3/8	3/16	100	45	180	39.4
110 4383	1	1-1/2	1/4	100	50	200	55.0
110 4614	1-1/4	1-7/16	3/32	50	30	120	22.5
110 4691	1-1/4	1-1/2	1/8	100	22	88	30.5
110 4768	1-1/4	1-5/8	3/16	50, 100	31	124	47.8
110 4845	1-1/4	1-3/4	1/4	50	45	180	66.5
110 4999	1-1/2	1-3/4	1/8	50, 100	19	76	36.0
110 5076	1-1/2	1-7/8	3/16	50, 100	26	104	56.1
110 5153	1-1/2	2	1/4	50	40	160	77.5
110 5307	1-3/4	2	1/8	50	16	64	41.5
110 5384	1-3/4	2-1/4	1/4	50	29	116	80.0
110 5461	2	2-1/4	1/8	50	14	56	47.1
110 5615	2	2-1/2	1/4	50	35	140	99.7
110 5769	2-1/4	2-3/4	1/4	50	24	96	111.0
110 5846	2-1/2	3	1/4	50	22	88	122.0
110 5923	3	3-1/2	1/4	50	19	76	144.0
110 6077	4	4-3/4	3/8	50	21	84	300.0

Add length suffix to part number when ordering. Example: 100 ft. of 1" I.D. x 1-1/4" O.D. tubing is part number 110 4152-100. Cut coils are available from coils of 100 ft. or less; charges apply — call for details. Coils over 100 ft. are sold by standard coil length only.

**BOLD** indicates the critical dimension for fittings application.

### Recommended Fittings & Clamps

- Cam operated couplings
- Thermobarb® barbed fittings
- Oetiker® ear type clamps
- Kwik Clamp™ nylon double bond hose clamps
- Worm gear clamps







## Thermobarb® Plastic Plastic Barbed Fittings in Five Materials

- Precision molded in nylon-6, high density polyethylene, PVDF, polypropylene, glass-fiber reinforced nylon, or glass-fiber reinforced polypropylene
- Lightweight, compact, easy to install and disconnect
- High impact strength
- Excellent chemical resistance



## Thermobarb® Brass Brass Barbed Fittings

- Formed of forged and/or machined brass
- Tapered pipe threads are made to Dryseal USA specifications
- An industrial standard — use in all general purpose applications
- May be used in potable water systems



## Cam-Operated Couplings Four Plastic Materials

- Select from Nylon (glass-fiber reinforced), Polypropylene (glass-fiber reinforced), FDA-grade PVDF, or FDA-grade Polypropylene
- Much lighter weight than metal counterparts
- Made to MIL-C-27487 dimensions — fully interchangeable with other materials made to the same standards regardless of material

## Request a PVC catalog

Inside you'll find details on all of NewAge Industries' PVC products. Catalogs for polyurethane, silicone, fluoropolymer, rubber, and semi-rigid tubing and hose are available, as well as barbed fittings and clamps, push-to-connect fittings, and custom products. Contact your NewAge Industries' sales representative or local distributor to request a copy of the catalog you need, or visit [www.newageindustries.com](http://www.newageindustries.com).



Clearflo, Kwik Clamp, Thermobarb, NewAge, "Fluid Transfer Specialists," and The "N" Logo are trademarks of NewAge® Industries, Inc. • Oetiker reg. TM Oetiker, Inc.

WARRANTY: NewAge Industries' products are warranted to be free from defects in material and workmanship. Any product found to carry such defects will be replaced without charge. This warranty is limited only to the replacement of NewAge Industries' products, item for item, which after examination by NewAge Industries are deemed defective. NewAge Industries specifically disclaims any other liability. The data supplied is provided as a helpful guideline and is believed to be reliable; however, nothing stated shall constitute a guarantee, recommendation, or warranty for any application.

NOTICE: NewAge Industries, Inc. has been a privately owned corporation since 1954. Neither the corporation nor its principals are affiliated, in any way, with any other group or entity either representing themselves as or being referred to by the term New-Age.

© NewAge Industries, Inc. 2010 Specifications are subject to change without notice.

1/5/10

**DISTRIBUTOR PARTNER**



145 James Way  
Southampton, PA 18966  
[www.newageindustries.com](http://www.newageindustries.com)

**800-50-NEWAGE**  
**(800-506-3924)**  
215-526-2300  
Fax: 800-837-1856  
215-526-2190  
[info@newageindustries.com](mailto:info@newageindustries.com)