

Polyethylene-Lined EVA

Co-Extruded Tubing of Polyethylene & EVA



Celebrating over


50
Years
of Service
1954-2008

ESOP Employee Owned
for Your Benefit



Fluid Transfer Specialists®

Co-Extruded Tubing of Polyethylene & EVA



- Made from Class VI, FDA-sanctioned ingredients for use with food and beverage contact surfaces
- Natural translucent color for visual contact with the flow
- Remains flexible at temperatures from -29°F to 160°F
- Non-toxic; odorless, tasteless, and inert
- Remains pliable even after extended contact with alcohol
- Good weatherability properties — resists U.V., ozone, gases, and moisture
- Low friction coefficient and excellent chemical resistance allows easy passage of solids, alcohols, acids, caustics and solvents



Made in U.S.A.

Notes

PE-LINED EVA (Ethylene Vinyl Acetate) tubing is designed for use where high purity is required. It also offers excellent chemical resistance and non-toxicity, while maintaining good flexibility. A co-extruded product, PE-LINED EVA is made of a low density polyethylene liner with an EVA outer jacket. It is manufactured in a patented process (Patent No. 4061461) to ensure the highest bond quality possible.

PE-LINED EVA tubing meets Class VI requirements and is suitable for use in poultry and meat processing. PE-LINED EVA also meets or exceeds standards in National Formulary, Vol. 14 for containers for injectables (plastics).

This product is an excellent substitute for PTFE, at working temperatures below 100°F, with cost savings of 50% or more. For working temperatures up to 180°F and greater stress resistance, ask about irradiated PE-LINED EVA tubing.

Physical Properties**

	PE Core	EVA Cover
Hardness, Shore D	50	
Hardness, Shore A		80
Tensile Strength, psi	2100	1500
Elongation at Break, %	550	750
Brittle Temperature, °F	-29	-159
Max. Operating Temp., °F	160	160
Color	Translucent	Translucent

**Values listed are typical for the material used in manufacture, except where noted, and are meant only as a guide to aid in design. Field testing should be performed to find the actual values for your application.

PART NO.	ID (IN.)	OD (IN.)	WALL (IN.)	WORKING PSI AT 70°F	BURST PSI AT 70°F	LBS. PER 100 FT.
410 0047*	1/8	3/16	1/32	43	129	.62
410 0075	1/8	1/4	1/16	71	213	1.51
410 0131	1/4	3/8	1/16	60	180	2.49
410 0215	3/8	1/2	1/16	50	150	3.49
410 0243*	3/8	5/8	1/8	66	198	7.99
410 0271*	1/2	5/8	1/16	32	96	4.48
410 0327	1/2	3/4	1/8	50	150	10.00
410 0467	3/4	1	1/8	39	118	13.96
410 0495	1	1-1/4	1/8	28	84	17.96

*Limited stock availability; lead times and minimums may apply — call for details. Sold by standard coil length only (50 ft.). Add length suffix to part number when ordering. Example: 50 ft. of 1/8" ID x 1/4" OD tubing is part number 410 0075-50. **BOLD** indicates the critical dimension for fittings application.

Recommended Fittings & Clamps

- Newloc® push-to-connect fittings
- Thermobarb® barbed fittings
- Oetiker® ear type clamps
- Kwik Clamp™ nylon double bond hose clamps
- Worm gear clamps

Custom Services

- **Cut** ■ **Overbraid**
- **Size** ■ **And More**

Call for more information
800-506-3924

Newloc, Kwik Clamp, Thermobarb, NewAge, "Fluid Transfer Specialists," and The "N" Logo are trademarks of NewAge® Industries, Inc. • Oetiker reg. TM Oetiker, Inc.

WARRANTY: NewAge Industries' products are warranted to be free from defects in material and workmanship. Any product found to carry such defects will be replaced without charge. This warranty is limited only to the replacement of NewAge Industries' products, item for item, which after examination by NewAge Industries are deemed defective. NewAge Industries specifically disclaims any other liability. The data supplied is provided as a helpful guideline and is believed to be reliable; however, nothing stated shall constitute a guarantee, recommendation, or warranty for any application.

NOTICE: NewAge Industries, Inc. has been a privately owned corporation since 1954. Neither the corporation nor its principals are affiliated, in any way, with any other group or entity either representing themselves as or being referred to by the term New-Age.

© NewAge Industries, Inc. 2008 Specifications are subject to change without notice.

8/15/08

DISTRIBUTOR PARTNER



145 James Way
Southampton, PA 18966
www.newageindustries.com

800-50-NEWAGE
(800-506-3924)
215-526-2300

Fax: 800-837-1856
215-526-2190

info@newageindustries.com